



STAINLESS STEEL  
**HAND SINKS**  
**SPECIAL PURPOSE**

Keyhole Bracket for easier installation and greater stability.



**Item #:** \_\_\_\_\_ **Qty #:** \_\_\_\_\_  
**Model #:** \_\_\_\_\_  
**Project #:** \_\_\_\_\_



7-PS-55



7-PS-64



7-PS-72



7-PS-727  
**CLASS 1 SECURITY  
 INSTALLATION**



7-PS-747  
**CLASS 2 SECURITY  
 INSTALLATION**

**FEATURES:**

One piece **Deep Drawn** sink bowl design.  
 Sink bowl is 10" x 14" x 5".  
 All sink bowls have a large liberal radii with a minimum dimension of 2" and are rectangular in design for increased capacity.  
 Keyhole wall mount bracket.  
 Stainless steel basket drain 1-1/2" IPS.  
 Splash mounted 4" O.C. gooseneck faucet furnished with aerator.

**Specific Features:**

**7-PS-55** features eye wash faucet attachment.  
**7-PS-64** features tubular support brackets.  
**7-PS-72** is H.A.C.C.P compliant hand sink featuring slow, self-closing, metering faucet with mixing valve.  
**7-PS-727** Unit totally enclosed. Bottom security panel provides access for installation and services. Vandal Proof Aerators. All fasteners are stainless steel tamper proof. Concealed drain. Heavy duty gooseneck faucet. Towel dispenser with hinged towel box with lock. Unit uses standard C-fold towels. Liquid Soap dispenser.  
**7-PS-747** Unit totally enclosed. Bottom security panel provides access for installation and services. Vandal Proof Aerators. All fasteners are stainless steel tamper proof. Concealed drain. Heavy duty gooseneck faucet.

**CONSTRUCTION:**

All TIG welded.  
 Welded areas blended to match adjacent surfaces and to a satin finish.  
 Die formed Countertop Edge with a 3/8" No-Drip offset.  
 One sheet of stainless steel - No Seams.

**MATERIAL:**

Heavy gauge type 304 series stainless steel.  
 Wall mounting bracket is galvanized and of offset design.  
 All fittings are brass / chrome plated unless otherwise indicated.

**MECHANICAL:**

Faucet supply is 1/2" IPS male thread hot and cold.

**Standard Faucet conforms to NSF 61 Standard 9. An optional faucet upgrade is required for compliance to AB 1953 Standards.**

For Replacement Faucets & Upgrades, Drains & Accessories visit our website at [www.advancetabco.com](http://www.advancetabco.com)



**Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.**

Email Orders To: [customer@advancetabco.com](mailto:customer@advancetabco.com). For Smart Fabrication™ Quotes, Email To: [smartfab@advancetabco.com](mailto:smartfab@advancetabco.com) or Fax To: 631-586-2933

**NEW YORK**  
 Fax: (631) 242-6900

**GEORGIA**  
 Fax: (770) 775-5625

**TEXAS**  
 Fax: (972) 932-4795

**NEVADA**  
 Fax: (775) 972-1578

# DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500" Interior: ± .250"

FITTINGS SUPPLIED AS SHOWN

ALL DIMENSIONS ARE TYPICAL

**7-PS-64**

**25 lbs.**

**7-PS-72**

**15 lbs.**

**7-PS-55**

**15 lbs.**

**EYE WASH DETAIL**

INVERTER VALVE (PULL KNOB TO ACTIVATE EYE WASH)

1 1/2" (38mm)

3" (76mm)

55/64"-27 FEMALE INLET

CHROME PLATED FORGED BRASS VALVE BODY

REMOVABLE AERATOR

AERATED OUTLET HEAD MAY BE ADJUSTED TO ANY DESIRED ANGLE

**7-PS-747**

**45 lbs.**

**Mounting Detail**

Washer

Nut

1/2" Threaded Rod

**7-PS-727**

**Unit with Towel Dispenser**

**Security Skirt Enclosure**

15-3/4"

23-1/4"

17-1/8"

15-1/8"

37"

