

Can Dispensing Racks

ITEM NO. _____
 QUANTITY NO. _____
 JOB NO. _____
 SPEC NO. _____

Specifications:

- Organizes can stock and maximizes available space. Self-feeding feature keeps stock rotated.
- Vertical uprights and cross braces are constructed of 1½" aluminum tubing.
- Half size racks available with stainless steel, aluminum or poly-top work surfaces.
- Mobile units are easily maneuvered on two 5" locking swivel and two 5" rigid polyurethane plate casters.



CR-162



CR-72M



CR-162M

EXPRESS

Model Number	Ordering Number	Type of Unit	Type of Top	Overall Dimensions						Can Capacity		Approx. Ship Weight	
				Width		Length		Height		#10	#5	(lb)	(kg)
				(in)	(mm)	(in)	(mm)	(in)	(mm)				
CR-162	112491	Stationary	None	25¼	641	35	889	71	1,803	162	216	60	27
CR-162AJ	112504	Adjustable											
CR-162M	112512	Mobile Work Station	None	27½	699	35	889	76	1,930	162	216	65	29
CR-54M	112521		Aluminum	27½	699	35	889	35	889	54	72	47	21
CR-54PT	112547		Poly Top									65	29
CR-54SS	112555		Stainless Steel									61	28
CR-72M	112563		Aluminum	27½	699	35	889	40	1,016	72	96	58	26
CR-72PT	112571		Poly Top									72	33
CR-72SS	112580		Stainless Steel									67	30
Replacement Caster Information													
738A	128784	Swivel Plate Caster with 5" Polyurethane Wheel										—	—
743A	128792	Rigid Plate Caster with 5" Polyurethane Wheel										—	—
7112	122180	5" Polyurethane Wheel										—	—

LABORATORY CERTIFICATION AND APPROVAL SYMBOLS:



Freight Class: 125

Can Dispensing Racks



439 Oak Street • Garden City, NY 11530 • Tel: 1-800-444-3595 • Fax: 516-222-0371
 www.winholt.com • sales@winholt.com

NEW YORK • TEXAS • CALIFORNIA • MICHIGAN