

E8610V & E8612V **HEAVY-DUTY ALUMINUM TRANSPORT CARTS**

Non-Insulated Aluminum with Universal Slides



Model	Capacity		Number	Tray Capacity* on			Overall Dimensions						Caster		Shipping	
Number			of Slide	Centers of:			Height Depth		Width		Diameter		Weight			
	18x26	12x20	Pairs	1-1/2"	3"	4-1/2"	in n	nm	in	mm	in	mm	in	mm	lbs	kgs
E8610V	1	2	10	20	15	10	59 ¹ / ₂ 1	511	31	787	26	660	5	127	151	68
E8612V	1	2	12	24	18	12	65 ¹ / ₂ 16	664	31	787	26	660	5	127	162	73

^{*}Standard capacity at 4-1/2" centers, adjustable on 1-1/2" centers.

CONSTRUCTION...Straight line modular styling with all seams hemmed-in for added strength & durability. Heavy gauge aluminum construction is heli-arc welded to form solid unit.

CABINET MATERIAL...Entire cabinet constructed on .080" thick aluminum. completely heli-arc welded and reinforced in the center of the cabinet with 1/4" x 1" tie rods. 2" x 1" x 1/8" thick specially extruded aluminum vertical uprights and 1-3/8" x 1" x 1/8" thick horizontal top supports are heli-arc welded for rigidity and support.

BASE FRAME...Constructed of .125" thick aluminum with heavy duty full width bolster pads. Entire base frame, including bolster pads, are heli-arc welded.

CASTERS...5" diameter plate mounted casters. All swivel.

DOOR...Face mounted, full length door constructed of .080" thick aluminum reinforced with 1" thick square tube vertical reinforcement channel. All sides are hemmed and completely heli-arc

HINGES...Heavy duty stainless stell butttype hinges with 3/8" diameter fix pin. 270 degree door swing.

TRAY SLIDES...Heavy duty universal type trays slides constructed of .125" thick aluminum. Fully adjustable at 1-1/2" centers with top, middle and bottom slides welded to uprights for additional support. Holds two 12"x20" pans or one 18"x26" tray per slide. Will also accommodate Gastronorm 2/1 pans (one per slide), 1/1 pans (2 per slide), and 20"x20" glass racks.

LATCH...Side mounted 12 gauge stainless steel door latch with 3/8" diameter pin for positive door closure.

ACCESSORIES/OPTIONS...

- ☐ Full perimeter bumper
- ☐ Polyurethane tread casters
- ☐ Floor lock
- ☐ 3-sided top rail
- ☐ Top mounted transport latch with padlock hasp
- ☐ Additional slide pairs

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN

1551 McCormick Ave., Mundelein, IL 60060 (847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981