



**LEGEND™**

**Heavy-Duty 36" (914mm) Gas Range**

Item No. \_\_\_\_\_

Project \_\_\_\_\_

Quantity \_\_\_\_\_

**(-7PL) Top Series**



Model 136-7PL

**SHORT/BID SPECIFICATION**

Range shall be a Montague *Legend* Model [Specify one]:

- 136-7PL**, with front-vented 40,000 BTU/hr conventional oven with counterweighted door, porcelainized steel interior, three-position rack guides and one wire pan rack standard
- V136-7PL**, with indirect-fired 45,000 BTU/hr convection oven with counterweighted door, porcelainized steel interior, five-position rack guides and three wire pan racks standard
- 36-7PL**, with open front cabinet base with two shelves
- M36-7PL**, with 28" (711mm) high modular stand with stainless steel tubular legs

...a 36" (914mm) wide heavy-duty gas-fired unit with a 19" (483mm) wide Spanish-style plancha with raised 3/4" (19mm) thick precision-ground cook surface, full perimeter grease trough with drop to grease receptacle and two 15,000 BTU/hr burners; plus one 12" (305mm) heavy-duty cast iron, precision-ground open top grate, over two 30,000 BTU/hr lift off star burners, provided with individual burner controls and automatic standing pilots; with stainless steel front and exterior bottom, black painted sides and back 4" (102mm) high flue riser and 3" (76mm) deep front rail standard; plus all the features listed and options/accessories checked:

**RANGE TOP FEATURES:**

One 19" wide x 25" deep (483mm x 635mm) Plancha [Spanish griddle] top, positioned left, with:

- 3/4" (19mm) thick precision-ground steel raised cook surface
- Full perimeter grease trough
- Two-quart hanging grease receptacle
- Two 15,000 BTU/hr burners with standing pilots
- Individual gas control valves for zoned heating

MODEL GUIDE		
Model No.	Base Style/Type	-7PL Range Top
136-7PL	With Standard Oven	
V136-7PL	With Convection Oven	
36-7PL	With Cabinet Base	
M36-7PL	With Modular Stand	

One 12" wide x 31" deep (305mm x 787mm) open burner top, positioned right, with:

- Heavily ribbed cast iron, surface-ground top grates
- Two large diameter 30,000 BTU/hr lift off star burners with raised ports
- Automatic, standing pilots
- Drip pan positioned under burners

**STANDARD (136-7PL MODEL) OVEN FEATURES:**

- 26" wide x 28" deep x 15" high (660mm x 711mm x 381mm) cooking compartment
- Accepts 18" x 26" (457mm x 660mm) pans sideways or lengthwise
- Front-venting oven design for more even cooking
- Heavy-duty counterweighted oven door — no springs
- Three-position adjustable nickel-plated rack supports, with one rack standard
- Interior panels and door porcelain lined for long life & easy cleaning
- Low-to-500°F (260°C) thermostat mounted in insulated cool zone
- 40,000 BTU/hr cast iron burner with automatic ignition safety pilot

**CONVECTION (V136-7PL MODEL) OVEN FEATURES:**

- 26" wide x 22-1/4" deep x 15" high (660mm x 565mm x 381mm) cooking compartment
- Muffled, indirect-fired design with blower, for fast-even cooking
- Heavy-duty counterweighted oven door — no springs
- Five-position adjustable nickel-plated rack supports, with three racks standard
- Interior panels and door porcelain lined for long life & easy cleaning
- Low-to-500°F (260°C) thermostat mounted in insulated cool zone
- 45,000 BTU/hr cast iron burner with automatic ignition safety pilot

**STANDARD CONSTRUCTION FEATURES:**

- Satin finish stainless steel front with 3" (76mm) deep front rail
- Other surfaces painted black with electrolytic zinc undercoating
- Stainless steel 4" (102mm) rear flue riser standard
- 6" (152mm) adjustable stainless steel legs standard (Except M36-7PL Model)
- 28" (711mm) stainless steel tubular legs standard with M36-7PL Model
- Cabinet base with sides, back panel and two shelves on 36-7PL Model
- 1-1/4 NPT front gas manifold with 1/2 union on each end

**STANDARD WARRANTY:**

- One Year, Parts & Labor
- Lifetime Warranty on Oven Door

**AGENCY APPROVALS**

- NSF Listed
- ETL Design Certified to ANSI Z83.11



HDS-14 [Rev. 10/10]

Item No. \_\_\_\_\_


Project \_\_\_\_\_

Quantity \_\_\_\_\_

# LEGEND™ Heavy-Duty 36" (914mm) Gas Range

## (-7PL) Top Series

Dimensions in brackets are millimeters



### OPTIONS GUIDE:

#### Open Burner Top Section:

- Front 30,000 BTU/hr lift off star burner with 15,000 BTU/hr rear solid top [-59]
- Cast Iron Ribbon Grate (for use with 20,000 BTU/hr lift off star burners only)
- 20,000 BTU/hr lift off star burner (2)
- 42" (1067 mm) range depth [Add Suffix: -40]
- 304 stainless steel burner box assembly

#### Back Panels/Shelves:

- 18" (457mm) high back
- Single high shelf
- Double high shelf
- 6" (152mm) wide stainless steel plate shelf
- 8" (203mm) wide stainless steel plate shelf

#### 19" (483mm) Plancha:

- 20,000 BTU/hr burners with 550°F (288°C) thermostats
- 1" (25mm) thick plate
- Polished chrome-plated cooking surface, only available with thermostats
- Top grooves to identify zoned heating areas

#### Oven:

- Cast iron oven bottom
- Extra oven racks: \_\_\_\_ea.

#### Manifolds: [Left rear with pressure regulator]:

- 1" NPT up to 400,000 BTU/hr
- Manifold Cap:**  left side  right side
- Stainless Manifold Cover:**  left side  right side

#### Finish:

- Stainless steel left side panel
- Stainless steel right side panel
- Stainless steel back panel
- Stainless steel exterior bottom
- Stainless steel shelves and sides [36-7PL Cabinet Model]

#### Electrical (V136):

- 120 V, 1-phase, 60 Hz, 3.4 A (standard, with 6' (1.8m) NEMA 5-15P power cord)
- 208-240 V, 1-phase, 60 Hz, 1.7 A

#### General:

- Casters — set of four 5" (127mm) casters

#### Flex Connector Kit [1"] NPT:

- 3' (914mm)  4' (1219mm)

**Security Options/Prison Package** [Consult Factory]

### INSTALLATION REQUIREMENTS & SHIPPING INFORMATION

- Ovens & ranges must be installed in accordance with local codes or in their absence with the National Fuel Gas Code: ANSI Z223.1; Natural Fuel Gas Code: CAN/CGA-B149.1 or Propane Installation Code: CAN/CGA-B149.2, as applicable. Compliance with codes is the responsibility of the Owner and Installer.
- An adequate ventilation system is required. Refer to National Fire Protection Association Standard No. 96, "Vapor Removal from Cooking Equipment."
- This appliance is intended for commercial use by professionally trained personnel. NOT intended for Residential Use.
- Specify installation elevation: \_\_\_\_\_ if above 2,000 ft (610m).
- GAS INLET SIZE (All Models):** 1-1/4" NPT front manifold with 1/2" union on each end provided for battery connection. A properly sized gas pressure regulator must be furnished by the Installer.
- The incoming gas line pressure into the regulator should be 8"-14" w.c. for natural gas, and 12"-14" w.c. for propane gas.

Minimum Clearances	Combustible Construction	Noncombustible Construction
From Back Wall*	2" (51mm)	0"
Left & Right Side**	15" (381mm)	0"
With 6" (152mm) legs	Suitable for installation on combustible floors	
*V136 Models require 2" (51 mm) for motor clearance at rear		

Specify Type of Gas:		<input type="checkbox"/> Natural	<input type="checkbox"/> Propane	Electrical	Shipping Weight	Shipping Class	Cube (Crated) ft <sup>3</sup> /m <sup>3</sup>
Gas Delivery Pressure:		6.0" WC	10.0" WC	120V			
Models:	Burners	BTU/hr* (kW)	BTU/hr* (kW)	Amperage			
136-7PL	5	130,000 (38.1)	130,000 (38.1)	---	636 lbs (288 kg)	85	32/.9
V136-7PL	5	135,000 (39.6)	135,000 (39.6)	3.4	660 lbs (299 kg)	85	32/.9
36-7PL	4	90,000 (26.4)	90,000 (26.4)	---	450 lbs (204 kg)	85	32/.9
M36-7PL	4	90,000 (26.4)	90,000 (26.4)	---	390 lbs (177 kg)	85	18/.5

Add 5,000 BTU/hr (1.5 kW) for thermostat controlled plancha burner.

Entry Clearance: 30" (762mm) uncrated, with legs removed [All Models]  
 Due to continuous product improvements, specifications are subject to change without notice.



**THE MONTAGUE COMPANY**  
 1830 Stearman Avenue, Hayward, CA 94545  
 800 345-1830 • Fax: 510 785-3342  
 www.montaguecompany.com

