



O8600 Series FIXED ANGLE TRAY RACKS

Standard and Wide Opening Racks for 18"x26" Trays

CARTER-HOFFMANN



FOOD SERVICE EQUIPMENT
FIXED ANGLE & OVAL TRAY RACKS

SPECIFICATIONS

Printed in U.S.A. J30 0609
Carter-Hoffmann is a trademark
of Carter-Hoffmann LLC

| Model Number | Tray Capacity | Tray Slide Spacing | | Overall Dimensions | | | | | | Caster Diameter | | Shipping Weight | |
|--|---------------|--------------------------------|-----|---------------------------------|------|--------------------------------|-----|--------------------------------|------|-----------------|-----|-----------------|-----|
| | | 18"x26" | | Height | | Depth | | Width | | in mm | | lbs kgs | |
| | | in | mm | in | mm | in | mm | in | mm | in | mm | lbs | kgs |
| <input type="checkbox"/> O8609 | 9 | 5 ¹ / ₁₆ | 129 | 55 | 1397 | 26 ¹ / ₄ | 667 | 20 ⁵ / ₈ | 524 | 5 | 127 | 77 | 35 |
| <input type="checkbox"/> O8611 | 11 | 5 ¹ / ₁₆ | 129 | 64 ³ / ₁₆ | 1630 | 26 ¹ / ₄ | 667 | 20 ⁵ / ₈ | 524 | 5 | 127 | 80 | 36 |
| <input type="checkbox"/> O8612 | 12 | 5 ¹ / ₁₆ | 129 | 69 ⁵ / ₁₆ | 1761 | 26 ¹ / ₄ | 667 | 20 ⁵ / ₈ | 524 | 5 | 127 | 82 | 37 |
| <input type="checkbox"/> O8616 | 16 | 3 | 76 | 57 ³ / ₁₆ | 1453 | 26 ¹ / ₄ | 667 | 20 ⁵ / ₈ | 524 | 5 | 127 | 85 | 39 |
| <input type="checkbox"/> O8618 | 18 | 3 | 76 | 64 ³ / ₁₆ | 1630 | 26 ¹ / ₄ | 667 | 20 ⁵ / ₈ | 524 | 5 | 127 | 87 | 40 |
| <input type="checkbox"/> O8620 | 20 | 3 | 76 | 69 ⁵ / ₁₆ | 1761 | 26 ¹ / ₄ | 667 | 20 ⁵ / ₈ | 524 | 5 | 127 | 90 | 41 |
| <input type="checkbox"/> O8622 ¹ | 22 | 5 ¹ / ₁₆ | 129 | 64 ³ / ₁₆ | 1630 | 26 ¹ / ₄ | 667 | 40 ¹ / ₈ | 1019 | 5 | 127 | 154 | 70 |
| <input type="checkbox"/> O8624 ¹ | 24 | 5 ¹ / ₁₆ | 129 | 69 ⁵ / ₁₆ | 1761 | 26 ¹ / ₄ | 667 | 40 ¹ / ₈ | 1019 | 5 | 127 | 157 | 71 |
| <input type="checkbox"/> O8636 ¹ | 36 | 3 | 76 | 64 ³ / ₁₆ | 1630 | 26 ¹ / ₄ | 667 | 40 ¹ / ₈ | 1019 | 5 | 127 | 159 | 72 |
| <input type="checkbox"/> O8640 ¹ | 40 | 3 | 76 | 69 ⁵ / ₁₆ | 1761 | 26 ¹ / ₄ | 667 | 40 ¹ / ₈ | 1019 | 5 | 127 | 165 | 75 |
| <input type="checkbox"/> O8609W ² | 9 | 5 ¹ / ₁₆ | 129 | 55 | 1397 | 18 ⁵ / ₈ | 473 | 28 ⁵ / ₈ | 727 | 5 | 127 | 77 | 35 |
| <input type="checkbox"/> O8611W ² | 11 | 5 ¹ / ₁₆ | 129 | 64 ³ / ₁₆ | 1630 | 18 ⁵ / ₈ | 473 | 28 ⁵ / ₈ | 727 | 5 | 127 | 80 | 36 |
| <input type="checkbox"/> O8612W ² | 12 | 5 ¹ / ₁₆ | 129 | 69 ⁵ / ₁₆ | 1761 | 18 ⁵ / ₈ | 473 | 28 ⁵ / ₈ | 727 | 5 | 127 | 82 | 37 |
| <input type="checkbox"/> O8616W ² | 16 | 3 | 76 | 57 ³ / ₁₆ | 1453 | 18 ⁵ / ₈ | 473 | 28 ⁵ / ₈ | 727 | 5 | 127 | 85 | 39 |
| <input type="checkbox"/> O8618W ² | 18 | 3 | 76 | 64 ³ / ₁₆ | 1630 | 18 ⁵ / ₈ | 473 | 28 ⁵ / ₈ | 727 | 5 | 127 | 87 | 40 |
| <input type="checkbox"/> O8620W ² | 20 | 3 | 76 | 69 ⁵ / ₁₆ | 1761 | 18 ⁵ / ₈ | 473 | 28 ⁵ / ₈ | 727 | 5 | 127 | 90 | 41 |

¹double width rack

²wide-opening rack; side-loaded trays



CONSTRUCTION...Heavy-duty, high tensile, all-welded extruded aluminum. Fully reinforced with horizontal stabilizing bars to prevent buckling. Entire base frame and bolster pads are completely welded to form solid one-piece unit.

CABINET MATERIAL...Type 6463-T5 alloy. Vertical and horizontal frame members are 1"x1" x .070 extruded aluminum tubing. Corner gussets constructed of 1-1/2" x 1-1/2" x 5/8" thick angle are welded to the inside angles (bottom side) where horizontal cross bracing meets vertical uprights.

ANGLE SLIDES... 1-1/2" x 1-7/8" wide angle type slide. Welded-in-place, both vertically and horizontally for support. Each slide is ribbed in order to minimize galling and flaking, as well as easy pan sliding.

CASTERS...Four 5" diameter heavy-duty polyurethane, plate mounted, non-marking casters. Caster plates welded to frame and bolted to caster plate. All swivel.

ACCESSORIES/OPTIONS...

- Caster locks (2)
- Corner bumpers (4)
- Pan stop
- Perimeter bumper
- Vertical bumpers
- Solid base

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN
1551 McCormick Ave., Mundelein, IL 60060
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com

Suburban Bowery



O1600 Series UNIVERSAL OVAL TRAY RACKS for Most Standard Oval Trays

CARTER-HOFFMANN
11
FOOD SERVICE EQUIPMENT
FIXED ANGLE & OVAL TRAY RACKS



| Model Number | Tray Capacity <i>see sizes below</i> | Tray Slide Spacing | | Overall Dimensions | | | Caster Diameter | | Shipping Weight | |
|---|---|--------------------|-----|-------------------------------------|----------------|-------------------------------------|-----------------|-----|-----------------|-----|
| | | in | mm | Height in mm | Depth in mm | Width in mm | in | mm | lbs | kgs |
| <input type="checkbox"/> O1610 | 10 | 6 | 152 | 70 1778 | 30 762 | 26 ¹ / ₂ 673 | 5 | 127 | 99 | 45 |
| <input type="checkbox"/> O1620 ¹ | 20 | 6 | 152 | 71 ⁵ / ₈ 1819 | 30 762 | 51 ³ / ₄ 1314 | 5 | 127 | 182 | 83 |

¹double width rack

CONSTRUCTION... Heavy-duty, high tensile, all-welded extruded aluminum. Fully reinforced with horizontal stabilizing bars to prevent buckling. Entire base frame and bolster pads are completely welded to form solid one-piece unit.

CABINET MATERIAL... Constructed of 1-1/4" x 1-1/2" x .070 wall tubing. Angle slides are 2" x 6-3/4" x .125" wall. Four welds per angle slide.

ANGLE SLIDES... 1-1/2" x 1-7/8" wide angle type slide. Welded-in-place, both vertically and horizontally for support. Each slide is ribbed in order to minimize galling and flaking, as well as easy pan sliding. Accepts oval tray sizes 20-3/4" x 25-1/2", 22-3/4" x 27-5/8" and 23-1/2" x 29".

CASTERS... Four 5" diameter platform casters. All swivel.

ACCESSORIES/OPTIONS...

- 5" polyurethane swivel platform caster
- Corner bumpers (4)
- Caster locks (2) for 5" platform casters
- Perimeter bumper
- Pan stop
- Vertical bumpers

SPECIFICATIONS

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN
1551 McCormick Ave., Mundelein, IL 60060
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com

Suburban Bowery

Printed in U.S.A. J30 0609
Carter-Hoffmann is a trademark
of Carter-Hoffmann LLC