



# O8600 Series FIXED ANGLE TRAY RACKS

Standard and Wide Opening Racks for 18"x26" Trays

CARTER-HOFFMANN



FOOD SERVICE EQUIPMENT  
FIXED ANGLE & OVAL TRAY RACKS

# SPECIFICATIONS

Printed in U.S.A. J30 0609  
Carter-Hoffmann is a trademark  
of Carter-Hoffmann LLC

Model Number	Tray Capacity	Tray Slide Spacing		Overall Dimensions						Caster Diameter		Shipping Weight	
		18"x26"		Height		Depth		Width		in mm		lbs kgs	
		in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kgs
<input type="checkbox"/> O8609	9	5 <sup>1</sup> / <sub>16</sub>	129	55	1397	26 <sup>1</sup> / <sub>4</sub>	667	20 <sup>5</sup> / <sub>8</sub>	524	5	127	77	35
<input type="checkbox"/> O8611	11	5 <sup>1</sup> / <sub>16</sub>	129	64 <sup>3</sup> / <sub>16</sub>	1630	26 <sup>1</sup> / <sub>4</sub>	667	20 <sup>5</sup> / <sub>8</sub>	524	5	127	80	36
<input type="checkbox"/> O8612	12	5 <sup>1</sup> / <sub>16</sub>	129	69 <sup>5</sup> / <sub>16</sub>	1761	26 <sup>1</sup> / <sub>4</sub>	667	20 <sup>5</sup> / <sub>8</sub>	524	5	127	82	37
<input type="checkbox"/> O8616	16	3	76	57 <sup>3</sup> / <sub>16</sub>	1453	26 <sup>1</sup> / <sub>4</sub>	667	20 <sup>5</sup> / <sub>8</sub>	524	5	127	85	39
<input type="checkbox"/> O8618	18	3	76	64 <sup>3</sup> / <sub>16</sub>	1630	26 <sup>1</sup> / <sub>4</sub>	667	20 <sup>5</sup> / <sub>8</sub>	524	5	127	87	40
<input type="checkbox"/> O8620	20	3	76	69 <sup>5</sup> / <sub>16</sub>	1761	26 <sup>1</sup> / <sub>4</sub>	667	20 <sup>5</sup> / <sub>8</sub>	524	5	127	90	41
<input type="checkbox"/> O8622 <sup>1</sup>	22	5 <sup>1</sup> / <sub>16</sub>	129	64 <sup>3</sup> / <sub>16</sub>	1630	26 <sup>1</sup> / <sub>4</sub>	667	40 <sup>1</sup> / <sub>8</sub>	1019	5	127	154	70
<input type="checkbox"/> O8624 <sup>1</sup>	24	5 <sup>1</sup> / <sub>16</sub>	129	69 <sup>5</sup> / <sub>16</sub>	1761	26 <sup>1</sup> / <sub>4</sub>	667	40 <sup>1</sup> / <sub>8</sub>	1019	5	127	157	71
<input type="checkbox"/> O8636 <sup>1</sup>	36	3	76	64 <sup>3</sup> / <sub>16</sub>	1630	26 <sup>1</sup> / <sub>4</sub>	667	40 <sup>1</sup> / <sub>8</sub>	1019	5	127	159	72
<input type="checkbox"/> O8640 <sup>1</sup>	40	3	76	69 <sup>5</sup> / <sub>16</sub>	1761	26 <sup>1</sup> / <sub>4</sub>	667	40 <sup>1</sup> / <sub>8</sub>	1019	5	127	165	75
<input type="checkbox"/> O8609W <sup>2</sup>	9	5 <sup>1</sup> / <sub>16</sub>	129	55	1397	18 <sup>5</sup> / <sub>8</sub>	473	28 <sup>5</sup> / <sub>8</sub>	727	5	127	77	35
<input type="checkbox"/> O8611W <sup>2</sup>	11	5 <sup>1</sup> / <sub>16</sub>	129	64 <sup>3</sup> / <sub>16</sub>	1630	18 <sup>5</sup> / <sub>8</sub>	473	28 <sup>5</sup> / <sub>8</sub>	727	5	127	80	36
<input type="checkbox"/> O8612W <sup>2</sup>	12	5 <sup>1</sup> / <sub>16</sub>	129	69 <sup>5</sup> / <sub>16</sub>	1761	18 <sup>5</sup> / <sub>8</sub>	473	28 <sup>5</sup> / <sub>8</sub>	727	5	127	82	37
<input type="checkbox"/> O8616W <sup>2</sup>	16	3	76	57 <sup>3</sup> / <sub>16</sub>	1453	18 <sup>5</sup> / <sub>8</sub>	473	28 <sup>5</sup> / <sub>8</sub>	727	5	127	85	39
<input type="checkbox"/> O8618W <sup>2</sup>	18	3	76	64 <sup>3</sup> / <sub>16</sub>	1630	18 <sup>5</sup> / <sub>8</sub>	473	28 <sup>5</sup> / <sub>8</sub>	727	5	127	87	40
<input type="checkbox"/> O8620W <sup>2</sup>	20	3	76	69 <sup>5</sup> / <sub>16</sub>	1761	18 <sup>5</sup> / <sub>8</sub>	473	28 <sup>5</sup> / <sub>8</sub>	727	5	127	90	41

<sup>1</sup>double width rack

<sup>2</sup>wide-opening rack; side-loaded trays



**CONSTRUCTION...**Heavy-duty, high tensile, all-welded extruded aluminum. Fully reinforced with horizontal stabilizing bars to prevent buckling. Entire base frame and bolster pads are completely welded to form solid one-piece unit.

**CABINET MATERIAL...**Type 6463-T5 alloy. Vertical and horizontal frame members are 1"x1" x .070 extruded aluminum tubing. Corner gussets constructed of 1-1/2" x 1-1/2" x 5/8" thick angle are welded to the inside angles (bottom side) where horizontal cross bracing meets vertical uprights.

**ANGLE SLIDES...** 1-1/2" x 1-7/8" wide angle type slide. Welded-in-place, both vertically and horizontally for support. Each slide is ribbed in order to minimize galling and flaking, as well as easy pan sliding.

**CASTERS...**Four 5" diameter heavy-duty polyurethane, plate mounted, non-marking casters. Caster plates welded to frame and bolted to caster plate. All swivel.

**ACCESSORIES/OPTIONS...**

- Caster locks (2)
- Corner bumpers (4)
- Pan stop
- Perimeter bumper
- Vertical bumpers
- Solid base

Specifications subject to change through product improvement & innovation.

**CARTER-HOFFMANN**  
1551 McCormick Ave., Mundelein, IL 60060  
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981  
[www.carter-hoffmann.com](http://www.carter-hoffmann.com)

Suburban Bowery



## O1600 Series UNIVERSAL OVAL TRAY RACKS for Most Standard Oval Trays



O1610

O1620

Model Number	Tray Capacity see sizes below	Tray Slide Spacing		Overall Dimensions			Caster Diameter		Shipping Weight	
		in	mm	Height in mm	Depth in mm	Width in mm	in	mm	lbs	kg
<input type="checkbox"/> O1610	10	6	152	70 1778	30 762	26 <sup>1</sup> / <sub>2</sub> 673	5	127	99	45
<input type="checkbox"/> O1620 <sup>1</sup>	20	6	152	71 <sup>5</sup> / <sub>8</sub> 1819	30 762	51 <sup>3</sup> / <sub>4</sub> 1314	5	127	182	83

<sup>1</sup>double width rack

**CONSTRUCTION...** Heavy-duty, high tensile, all-welded extruded aluminum. Fully reinforced with horizontal stabilizing bars to prevent buckling. Entire base frame and bolster pads are completely welded to form solid one-piece unit.

**CABINET MATERIAL...** Constructed of 1-1/4" x 1-1/2" x .070 wall tubing. Angle slides are 2" x 6-3/4" x .125" wall. Four welds per angle slide.

**ANGLE SLIDES...** 1-1/2" x 1-7/8" wide angle type slide. Welded-in-place, both vertically and horizontally for support. Each slide is ribbed in order to minimize galling and flaking, as well as easy pan sliding. Accepts oval tray sizes 20-3/4" x 25-1/2", 22-3/4" x 27-5/8" and 23-1/2" x 29".

**CASTERS...** Four 5" diameter platform casters. All swivel.

**ACCESSORIES/OPTIONS...**

- 5" polyurethane swivel platform caster
- Corner bumpers (4)
- Caster locks (2) for 5" platform casters
- Perimeter bumper
- Pan stop
- Vertical bumpers

Specifications subject to change through product improvement & innovation.

**CARTER-HOFFMANN**  
1551 McCormick Ave., Mundelein, IL 60060  
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981  
[www.carter-hoffmann.com](http://www.carter-hoffmann.com)

Suburban Bowery

CARTER-HOFFMANN  
**11**  
FOOD SERVICE EQUIPMENT  
FIXED ANGLE & OVAL TRAY RACKS

# SPECIFICATIONS

Printed in U.S.A. J30 0609  
Carter-Hoffmann is a trademark  
of Carter-Hoffmann LLC