



Project name:	
Location:	
Item:	Qty:
Model:	

Ideally suited for smoothie and ice-cream shops, small spaces, counter-top bars, mobile carts, food courts, lounges, boats, caterers, dental offices, day-care operators, guest houses, room service, espresso bars, kiosks, laboratories and much more !

# F-14

## MULTI-PURPOSE COUNTER-TOP WAREWASHER

*Use as  
an assorted  
Warewasher ...*

Accessory  
No. 30035,  
15-place insert for  
saucers and/or  
small plates

Accessory  
No. 30026  
Cutlery Holder



*... or as a Glasswasher*

Accessory No. 30132,  
9-place insert for glass ware

*Note: Optional accessory No. 30133,  
16-place insert for glass ware*



*... or as a Dishwasher*

Accessory No. 30037,  
6-place insert for  
plates up to 10 1/2" in diameter



*... or for blender containers*

Accessory No. 30131,  
4-place insert



## PERFORMANCE FEATURES

- Completely automatic wash and rinse cycles including one wash program at 150°F. (65°C.) and one rinse program at 185°F. (85°C.)
- Hourly production: 20 racks of various items OR depending on rack insert used, the following quantities can be washed and rinsed:
  - 4-place insert for Blender Containers - 80 / hr.
  - 9-place insert for Glassware - 180 / hr.
  - 16-place insert for Glassware - 320 / hr.
  - 6-place insert for Dishes - 120 / hr.
- Built-in automatic detergent pump for consistent results each time
- Built-in automatic rinse-additive pump for sparkling final results

## CONSTRUCTION FEATURES

- Body, external housing, wash tank, and all chassis components in brushed stainless steel 304 18/10
- Constructed of insulated double-walled panels for low heat and noise emissions
- Unique and compact size for easy placement on a counter top, stand or mobile cart
- Door opening is designed to accept items up to a maximum height of 11"
- Integrated stainless steel booster with insulated lining
- Full width interior scrap screens of durable stainless steel
- Internal screen for protection of motor-pump
- Safety micro-switch on the door to interrupt wash pump action
- Lower revolving wash and rinse arm with lateral upper fixed rinse arms built of fiberglass designed for maximum results and ease of maintenance
- Independently-operated heating elements alternating between the booster and wash tank
- Both alternating heating elements serve to reduce overall energy costs by lowering amperage consumption
- Thermostatic regulated control of both wash and rinse water
- Automatic fill and water level regulation of the wash tank
- Individual digital gauges for both wash and rinse temperatures
- Vertical integrated control panel for simple access and technical maintenance



3560 NW 56th Street  
Fort Lauderdale, FL, United States 33309  
Telephone: 786.600.4687 / Toll Free: 844.218.8477  
Fax: 786.661.4100

5659 Royalmount Ave.  
Montreal, QC, Canada H4P 2P9  
Telephone: 514.737.9701 / Toll Free: 888.275.4538  
Fax: 514.342.3854 / Toll Free: 877.453.8832  
sales@mvpgroupcorp.com / mvpgroupcorp.com

Warranty: 90 days on labor and 1 year on parts. Certain conditions apply. See Owner's Manual for details.

## TECHNICAL FEATURES

- **Rack capacity:** 13.75" x 13.75" (350 mm x 350 mm)
- **Complete operating cycle:** 165 seconds wash and 15 seconds rinse
- **Wash tank capacity:** 2.1 U.S. gallons (8 litres)
- **Wash tank element:** 1400 watts (1.4 Kw)
- **Wash temperature:** 150°F (65°C)
- **Booster capacity:** 0.53 U.S. gallons (2.0 litres)
- **Booster element:** 1400 watts (1.4 Kw)
- **Rinse (water) temperature:** 185°F (85°C)
- **Maximum power absorption:** 1500 watts (1.5 Kw)
- **Wash motor-pump:** 100 watts
- **Power supply :** 110 Volt / 60 Hz  
(power cord with NEMA 5-20 plug included)
- **Optional:** 220 Volt / 50 Hz - **Special Order**  
(power cord and plug included)
- **Amperage:** Single phase - 13.5A
- **Water consumption:** 0.5 U.S. gallons per cycle (2.9 litres)
- **Recommended pressure:** 30 p.s.i. (dynamic)
- **Water inlet connection:** 3/4" male garden hose fitting (hose included)
- **Drain connection:** 1" ID hose connection (hose included)
- **Shipping weight:** 72 lbs (32.8 kg)

## ACCESSORIES

F-14 supplied with:

- (1) open rack - 13.75" x 13.75" (350 mm. X 350 mm.)
- (1) 4-place insert #30131 for blender containers
- (1) 9-place insert #30132 for glassware
- (1) 6-place insert #30037 for plates up to 10.5" diameter
- (1) 15-place insert #30035 for saucers and/or small plates
- (1) cutlery holder #30026
- **Optional:**
  - 16-place insert #30133 for glassware
  - Drain water tempering kit
  - Pressure reducing valve (PRV) kit

