

Millivolt Control

SPLIT TANK GAS FRYERS

IGF-40/40-2



- The Ikon Gas Fryer line has a tube heat exchange design that incorporates fast temperature recovery and large cold zone.
 - 30,000 BTU / burner
 - Models: 4 tubes, 2 split tanks.
 - 2 set individual gas control system for 2 split tanks.
 - Millivolt (snap action) thermostat, 200°F 400°F
 - Stainless steel front and door
 - Sides and back are galvanized steel
 - Large cold zone to trap food particles
 - 1 1/4" dia full port drain valve for fast and complete oil draining
 - 2" diameter adjustable Stainless Steel legs standard, casters optional
 - Tank is fully peened for smoother welds & easy cleaning
 - Drain pipe holder attached to inside door
 - Twin nickel plated baskets




















Millivolt Control

SPLIT TANK GAS FRYERS

IGF-40/40-2







Legs adjustable from 6" - 7 1/2" total leg height.

Specifications

Model	Width			Depth		Height		Clearance		Weight	Shipping	Ship.
	Α	В	С	D	Е	F	G	Н	I		Dimenisons	Weight
IGF4040LP/NG	20.9" 53cm	9" 22.8cm	34.5" 87.6cm	17.9" 45.5cm	39.75" 101cm	34.66" 88cm	6" 13cm	4.55" 11.6cm	6.25" 16.3cm	192 lbs 87kg	22.1/2"W x 36.1/4"D x 33.1/2"H (57cm x 92cm x 85cm)	205 lbs (93kg)

Model	Oil	Gas	Heat	Tube	Total	Number of
	Capacity	Type	Tubes	BTU's	BTU's	Burners
IGF4040LP	(36-39 lbs)*2	LPG	4	30,000	120,000	4
IGF4040NG	(36-39 lbs)*2	Natural	4	30,000	120,000	4

GAS REQUIREMENTS

- . 3/4" NPT gas connection. NG gas 4" W.C. ; LP gas 10"W.C.

